



Uptown – First Street

SPECIFICATIONS

Product Line	Uptown – First Street
Construction	Luxury Vinyl Plank
Class	ASTM F1700, Class III, Type B
Wearlayer Thickness	6 mil
Overall Thickness	2 mm – 0.079”
Nominal Dimensions	6” wide x 36” long
Finish	UV-Polyurethane
Installation	Glue down
Recommended Adhesive	Urban Surfaces Residential LVT / LVP Adhesive
Indoor Air Quality	FloorScore® Certified
LEED Scorecard	EQ4.3

PACKAGING

Square Feet per Carton	36
Pieces per Carton	24
Weight per Carton	28 lbs

TESTING

Slip Resistance / ASTM D2047	ADA Compliant
Static Load / ASTM F970-07	Passes
Radiant Flux / ASTM E648	Class I
Abrasion Resistance / ASTM D3389	Passes
Light Resistance / ASTM F1515	Passes
Heat Resistance / ASTM F1514	Passes
Chemical Resistance / ASTM F925	Passes
Surface Burning / ASTM E84	Passes
Smoke Density / ASTM E662-09	Passes

WARRANTY

Manufacturer’s Warranty	Lifetime
Residential Warranty	5 Year

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.