



DESCRIPTION: TAYLOR 2025 UNIVERSAL PRIMER

Taylor 2025 is an acrylic latex solution made for use as a primer coat on concrete, plywood, floor patch, acoustical concrete and other porous surfaces to prevent over absorption of adhesives and to insure a better bond of the adhesive to the subfloor. It is also designed to neutralize excess alkali.

FLOOR PREPARATION

Floor must be sound, smooth, clean, level, and dry. It must be free of dust, dirt, grease, oil, paint, old adhesive, incompatible curing compounds or sealers, fire retardant chemicals, release agents, or any other foreign substance that might interfere with a good bond. Floor should be vacuumed or swept clean prior to application of the 2025 primer.

INSTRUCTIONS

1. Pour primer onto substrate. Spread evenly with a broom or paint roller. For larger jobs, 2025 can be applied with a garden sprayer, airless rig or regular spray equipment. On very porous concrete a second coat may be necessary.
2. For alkali remediation, allow floor to dry after application of the 2025 and re-check pH. If pH is still high, a second application is needed.

PHYSICAL PROPERTIES

- Base: Acrylic Latex
Appearance: Cream liquid
Odor: Sweet aromatic - mild
Open Time: Up to 1 hour depending on the porosity of the subfloor.
Shelf Life: One year in unopened container at 70°F
Coverage: Up to 500 sq. ft. per gallon
Flammability: Non-flammable, qualified for NFPA Class A and UBC Class 1 fire ratings as determined by the ASTM E84 Tunnel Test.
Features: Solvent-free, non-flammable, freeze/thaw stable to 10°F (-12°C). Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.
Clean Up: Use soap and water while wet. Use Taylor Touchdown #9 Adhesive Remover/Stripper when dry.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Technical Services at 800-868-4583; visit us on the web at www.wftaylor.com; or e-mail us at info@wftaylor.com.