

SPECIFICATIONS

PRODUCT LINE	SOUND-TEC PLUS
CONSTRUCTION	STONE POLYMER COMPOSITE (SPC)
CLASS	ASTM F1700, CLASS III, TYPE B
WEAR LAYER THICKNESS	20 MIL
EDGE	PAINTED BEVELED
OVERALL THICKNESS	6 MM – 0.236”
UNDERLAYMENT ATTACHED	YES
SIZE	9” WIDE X 60” LONG
FINISH	UV-POLYURETHANE
INSTALLATION	FLOATING

PACKAGING

SQUARE FEET PER CARTON	22.25
PIECES PER CARTON	6
WEIGHT PER CARTON	42 lbs
CARTONS PER PALLET	48

TESTING

SLIP RESISTANCE / ASTM D2047	≥ 0.5 (DRY)
RADIANT FLUX / ASTM E648	CLASS I
STATIC LOAD / ASTM F970-07	PASSES
ABRASION RESISTANCE / ASTM D3389	PASSES
LIGHT RESISTANCE / ASTM F1515	PASSES
HEAT RESISTANCE / ASTM F1514	PASSES
CHEMICAL RESISTANCE / ASTM F925	PASSES
SURFACE BURNING / ASTM E84	PASSES
SMOKE DENSITY / ASTM E662-09	PASSES

WARRANTY

RESIDENTIAL WARRANTY	LIFETIME
LIGHT COMMERCIAL WARRANTY	20 YEAR
COMMERCIAL WARRANTY	15 YEAR

ENVIRONMENTAL

INDOOR AIR QUALITY	FLOORSORE® CERTIFIED
LEED SCORECARD	EQ4.3
CHPS 01350	PASSES
PTHALATES	PASSES

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.