



## SPECIFICATIONS

Product Line	Sound-Tec
Construction	Stone Polymer Composite (SPC)
Class	ASTM F1700, Class III, Type B
Wear layer Thickness	20 mil
Edge	Beveled
Overall Thickness	6 mm – 0.236"
Size	7" wide x 48" long
Finish	UV-Polyurethane + EZ-Clean
Installation	Floating

## PACKAGING

Square Feet per Carton	23.47
Pieces per Carton	10
Weight per Carton	45 lbs
Cartons per Pallet	50

## PERFORMANCE TESTING

Slip Resistance / ASTM D2047	≥ 0.5 (Dry)
Radiant Flux / ASTM E648	Class I
Static Load / ASTM F970-07	Passes
Abrasion Resistance / ASTM D3389	Passes
Light Resistance / ASTM F1515	Passes
Heat Resistance / ASTM F1514	Passes
Chemical Resistance / ASTM F925	Passes
Smoke Density / ASTM E662-09	Passes

## WARRANTY

Manufacturer's Warranty	Lifetime
Residential Warranty	10 Year
Commercial Warranty	5 Year

## ENVIRONMENTAL

Indoor Air Quality	FloorScore® Certified
LEED Scorecard	EQ4.3
CHPS 01350	Passes

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.