

SPECIFICATIONS

PRODUCT LINE	LEVEL 7
CONSTRUCTION	VINYL
CLASS	ASTM F1700, CLASS III, TYPE B
WEAR LAYER THICKNESS	20 MIL
EDGE	BEVELED
OVERALL THICKNESS	3 MM – 0.118"
SIZE	7" WIDE X 48" LONG
FINISH	UV-POLYURETHANE
INSTALLATION	GLUE DOWN
RECOMMENDED ADHESIVE	URBAN 3020

PACKAGING

SQUARE FEET PER CARTON	34.6
PIECES PER CARTON	14
WEIGHT PER CARTON	41 LBS
CARTONS PER PALLET	65

TESTING

SLIP RESISTANCE / ASTM D2047	≥ 0.6 (DRY)
RADIANT FLUX / ASTM E648	CLASS I
STATIC LOAD / ASTM F970-07	PASSES
ABRASION RESISTANCE / ASTM D3389	PASSES
LIGHT RESISTANCE / ASTM F1515	PASSES
HEAT RESISTANCE / ASTM F1514	PASSES
CHEMICAL RESISTANCE / ASTM F925	PASSES
SURFACE BURNING / ASTM E84	PASSES
SMOKE DENSITY / ASTM E662-09	PASSES

WARRANTY

RESIDENTIAL WARRANTY	LIFETIME
LIGHT COMMERCIAL WARRANTY	20 YEAR
COMMERCIAL WARRANTY	10 YEAR

ENVIRONMENTAL

INDOOR AIR QUALITY	FLOORSORE® CERTIFIED
LEED SCORECARD	EQ4.3
CHPS 01350	PASSES
PTHALATES	PASSES

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.