

SPECIFICATIONS

| | |
|------------------------------|-------------------------------|
| PRODUCT LINE | SOUND-TEC TILE |
| CONSTRUCTION | STONE POLYMER COMPOSITE (SPC) |
| CLASS | ASTM F1700, CLASS III, TYPE B |
| WEAR LAYER THICKNESS | 20 MIL |
| EDGE | BEVELED |
| OVERALL THICKNESS | 6 MM – 0.236” |
| UNDERLAYMENT ATTACHED | YES |
| SIZE | 12” WIDE X 24” LONG |
| FINISH | UV-POLYURETHANE |
| INSTALLATION | FLOATING |

PACKAGING

| | |
|-------------------------------|--------|
| SQUARE FEET PER CARTON | 24 |
| PIECES PER CARTON | 12 |
| WEIGHT PER CARTON | 46 lbs |
| CARTONS PER PALLET | 66 |

TESTING

| | |
|---|-------------|
| SLIP RESISTANCE / ASTM D2047 | ≥ 0.5 (DRY) |
| RADIANT FLUX / ASTM E648 | CLASS I |
| STATIC LOAD / ASTM F970-07 | PASSES |
| ABRASION RESISTANCE / ASTM D3389 | PASSES |
| LIGHT RESISTANCE / ASTM F1515 | PASSES |
| HEAT RESISTANCE / ASTM F1514 | PASSES |
| CHEMICAL RESISTANCE / ASTM F925 | PASSES |
| SURFACE BURNING / ASTM E84 | PASSES |
| SMOKE DENSITY / ASTM E662-09 | PASSES |

WARRANTY

| | |
|---------------------------|----------|
| RESIDENTIAL WARRANTY | LIFETIME |
| LIGHT COMMERCIAL WARRANTY | 20 YEAR |
| COMMERCIAL WARRANTY | 15 YEAR |

ENVIRONMENTAL

| | |
|--------------------|----------------------|
| INDOOR AIR QUALITY | FLOORSORE® CERTIFIED |
| LEED SCORECARD | EQ4.3 |
| CHPS 01350 | PASSES |
| PTHALATES | PASSES |

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.