



SPECIFICATIONS

Product Line	Surface Guard	Finish	Titania
Construction	Stone Polymer Composite (SPC)	Installation	Floating
Wear Layer Thickness	Titania	Clip System	EZ Lock
Embossing	Natural Wood Texture	Underlayment	Sound Reducing
Edge Profile	Painted Bevel	Sound Properties	STC 61 / IIC 60
Overall Thickness	8mm (0.314")	Bacteria Resistance	Standard
Size (Imperial)	9.37" x 49.8"	Size (Metric)	238mm x 1264.92mm

PACKAGING

Pieces per Carton	5	Cartons per Container	1040
Square Feet per Carton	16.2 sqft	Square Feet per Container	16848 sqft
Square Meters per Carton	1.51 m2	Square Meters per Container	1565.23 m2
Weight per Carton (Imperial)	44.31 lbs	Weight per Container (Imperial)	46082.4 lbs
Weight per Carton (Metric)	20.1 kg	Weight per Container (Metric)	20902.63 kg
Cartons per Pallet	52	Weight per Pallet (Imperial)	2304.12 lbs
Square Feet per Pallet	842.4 sqft	Weight per Pallet (Metric)	1045.13 kg
Square Meters per Pallet	78.26 m2		

TESTING & SAFETY

Slip Resistance	ASTM D2047	>0.86 (DRY)
Radiant Flux	ASTM E648	CLASS 1
Smoke Density	ASTM E662	PASSES
Static Load	ASTM F970	2,000 PSI .009 INCH
Light Resistance	ASTM F1515	PASSES
Heat Resistance	ASTM F1514	PASSES
Chemical Resistance	ASTM F925	PASSES
Phthalates	ASTM F3414 - 20 (CPSC)	PASSES
Heavy Metals	ASTM F963	PASSES
Formaldehyde	ASTM D6007	PASSES
FloorScore Certified	California 01350	PASSES
Leed Scorecard	Eq4.3 Low-Emitting Materials	1 POINT

WARRANTY

Residential	Lifetime
Light Commercial	Lifetime
Commercial	Lifetime

THE MODERN FLOORING SOLUTION